



# 32" Open Frame Monitor

## GHK-32IP-TC

### FEATURES

- SVGA (1920 x 1080) (360 cd/m2)
- VGA & DVI Signal Input
- OSD Control on the Back Side
- 220V Power Input
- Integrated Industry-Standard Design



RoHS



32 inch  
TFT



OEM  
ODM

## PRODUCT SPECIFICATIONS

LCD	
Panel Type	LCD Panel (Optional)
Resolution (pixel)	1920*1080 (高清)
Display Area (mm)	697.68(H)x329.25(V)
Brightness (nit)	360nit (Optional)
Contrast Ratio	4000:1
Colors	16.7M
View Angle (U/D/L/R)	89/89/89/89
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	IR (单点免驱型)
Resolution(pixel)	4096*4096
Transmittance	>90%
Interface	
Signal Input	VGA+DVI ( 15 Pin D-sub/DVI-D Connector )
Touch Connectors	NO
Power	
Power Input	220V(50~60HZ)
Power Consumption	≤48W
Mechanical	
Material	High Strength Cold Rolling Steel Chassis
Mounting	Support Embedded Mounting
Dimensions	760.0(H) x 450.0(V) x 85.9(D)
Environment	
Operating Temp	0~50C°
Storage Temp	-20~60C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-32OP-NB	32"Open Frame Monitor with VGA/DVI input and power adapter (450nit)
GHK-32IP-TC	32"Open Frame Touch Monitor with Infrared touch screen,VGA/DVI input (450nit)

## DIMENSIONS

