

GHK-17IP-TA001

FEATURES

- SXGA (1280 x 1024) (380 cd/m2)
- VGA & DVI Signal Input
- OSD Control on the Front Side
- DC 12V Power Input
- Support VESA Wall Mount and Embedded Mount



RoHS



17 Inch TFT

WT

IP65

PRODUCT SPECIFICATIONS

LCD	
Panel Type	AU LCD Panel (Optional)
Resolution (pixel)	1280*1024
Display Area (mm)	337.920(H)x270.336V
Brightness (nit)	380nit
Contrast Ratio	1000:1
Colors	16.2M / 262k colors
View Angle (U/D/L/R)	85/85/85/85
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	5 Wire Resistive(Optional)
Resolution(pixel)	4096*4096
Transmittance	>90%
Interface	
Signal Input	VGA+DVI (15 Pin D-sub/DVI-D Connector)
Touch Connectors	USB / RS232(Optional)
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm)
Power Consumption	≤48W
Mechanical	
Material	Steel chassis & Aluminum front panel
Mounting	Support VESA Wall Mount and Embedded Mount
Dimensions	435.0(H) x 358.0(V) x 59.0(D)
Environment	
Operating Temp	0~50C°
Storage Temp	-20~60C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-17IP-NA001	17"Industry Monitor with VGA/DVI input and power adapter (1280*1024/ 380nit)
GHK-17IP-TA001	17"Industry Touch Monitor with 4wire resistive touch screen,VGA/DVI input (1280*1024 / 380nit)

DIMENSIONS

