

## GHK-19OP-NA

### FEATURES

- SVGA (1280 x 1024) (450 cd/m2)
- VGA & DVI Signal Input
- 5 Wire Resistive Touch Screen (Optional)
- OSD Control on the Back Side
- DC 12V Power Input
- Integrated Industry-Standard Design
- Support Embedded Mounting



### PRODUCT SPECIFICATIONS

LCD	
Panel Type	AU LCD Panel (Optional)
Resolution (pixel)	1280*1024
Display Area (mm)	376.32(H)x301.06(V)
Brightness (nit)	450nit (Optional)
Contrast Ratio	1000:1
Colors	16.7M
View Angle (U/D/L/R)	80/80/85/85
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	NO( Optional)
Resolution(pixel)	NO
Transmittance	NO
Interface	
Signal Input	VGA+DVI ( 15 Pin D-sub/DVI-D Connector ) AV Input / Video Input /Audio Input (Optional)
Touch Connectors	NO(Optional)
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm) & 3-PIN Industrial Connectors
Power Consumption	≤48W
Mechanical	
Material	High Strength Cold Rolling Steel Chassis
Mounting	Support Embedded Mounting
Dimensions	425.0(H) x 364.0(V) x 49.5(D)
Environment	
Operating Temp	0~50C°
Storage Temp	-20~60C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-19OP-NA	19"Open Frame Monitor with VGA/DVI input and power adapter (450nit)
GHK-19OP-TA	19"Open Frame Touch Monitor with 5wire resistive touch screen,VGA/DVI input (450nit)

### DIMENSIONS

